

R4

SAE 100 R4



内胶层：耐油合成橡胶
 增强层：2 层纤维增强层带螺旋钢丝
 外胶层：耐天候合成橡胶
 主要应用：吸气管，回油管

连续作业：-40℃~+100℃ -40°F~+212°F
 最高工作温度：121℃ 250°F
 建议使用流体介质：矿物油、菜油和油菜籽油、
 二醇和聚乙二醇基油、合成酯基油、水 / 乳化油

													
HOSE SIZE		R.O.D		O.D		MAX W.P		BURST PRESSURE		MIN.BEND RADIUS		WEIGHT	
DN	inch	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	g/m	lb/ft
16	5/8"	-	-	26.0	0.02	21	300	64	930	96	3.78	590	0.40
19	3/4"	-	-	29.0	1.14	21	300	84	1220	125	4.92	550	0.37
25	1"	-	-	35.0	1.38	17	250	70	1010	150	5.91	680	0.46
31	1.1/4"	-	-	42.0	1.65	14	200	56	810	200	7.87	840	0.56
36	1.1/2"	-	-	48.5	1.91	10	140	42	610	254	10.00	1024	0.70
51	2"	-	-	61.5	2.42	7	100	28	410	300	11.81	1420	0.95
63	2.1/2"	-	-	76.0	2.99	4	62	17	250	355	13.98	2150	1.44
76	3"	-	-	88.0	3.46	4	56	16	230	457	17.99	2850	1.91
89	3.1/2"	-	-	103.0	4.06	3	45	12	180	530	20.87	3450	2.31
102	4"	-	-	115.0	4.53	2	35	10	140	610	24.02	3900	2.61