

精密无缝钢管

公差符合 DIN EN 10305-4

碳钢白锌	管外径 (mm)	公差	壁厚	管内径	设计压力bar		爆破压力 bar	重量 kg/m
					DIN2413 1 静态	DIN 2413 III 动态		
R04×0.5	4	±0.08	0.50	3.00	313	273	1160	0.047
R04×0.75	4	±0.08	0.75	2.50	470	391	1820	0.063
R04×1	4	±0.08	1.00	2.00	627	500	2700	0.074
R05×1	5	±0.08	1.00	3.00	501	416	2120	0.099
R06×0.75	6	±0.08	0.75	4.50	333	288	1150	0.103
R06×1	6	±0.08	1.00	1.00	444	372	1650	0.123
R06×1.5	6	±0.08	1.50	3.00	666	526	2550	0.166
R06×2	6	±0.08	2.00	2.00	692	662	>3500	0.197
R06×2.5	6	±0.08	2.50	1.50	757	725	>3500	0.208
R08×1	8	±0.08	1.00	6.00	333	288	1175	0.173
R08×1.5	8	±0.08	1.50	5.00	499	412	1925	0.24
R08×2	8	±0.08	2.00	4.00	666	526	2500	0.296
R08×2.5	8	±0.08	2.50	3.00	658	630	2650	0.339
R10×1	10	±0.08	1.00	8.00	282	248	900	0.222
R10×1.5	10	±0.08	1.50	7.00	423	357	1450	0.314
R10×2	10	±0.08	2.00	6.00	564	458	2025	0.395
R10×2.5	10	±0.08	2.50	5.00	705	551	2675	0.462
R10×3	10	±0.08	3.00	4.00	666	638	>3500	0.518
R12×1	12	±0.08	1.00	10.00	235	209	750	0.271
R12×1.5	12	±0.08	1.50	9.00	353	303	1150	0.388
R12×2	12	±0.08	2.00	8.00	470	391	1600	0.493
R12×2.5	12	±0.08	2.50	7.00	588	474	2025	0.586
R12×3	12	±0.08	3.00	6.00	705	551	2600	0.666
R12×3.5	12	±0.08	3.50	5.00	651	624	0	0.734
R14×1.5	14	±0.08	1.50	11.00	302	264	975	0.462
R14×2	14	±0.08	2.00	10.00	403	342	1325	0.592
R14×2.5	14	±0.08	2.50	9.00	504	415	1650	0.709
R14×3	14	±0.08	3.00	8.00	604	485	2200	0.814
	14	±0.08	3.5	7.00	705	551	2625	0.906
R15×1	15	±0.08	1.00	13.00	188	170	575	0.345
R15×1.5	15	±0.08	1.50	12.00	282	248	950	0.499