

3TE

DIN EN 8533TE



内胶层：耐油合成橡胶
 增强层：2层高抗拉纤维编织外
 胶层：耐天候合成橡胶
 主要应用：低压管，回油管

连续作业：-40 ~+100
 最高工作温度：121
 建议使用流体介质：矿物油、菜油和
 油菜籽油、二醇和聚乙二醇基油、合
 成酯基油、水/乳化油

HOSE SIZE		R.O.D		O.D		MAX W.P		RURST PRESSURE		MIN.BEND RADIUS		WEIGHT	
DN	inch	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb/ft
6	1/4"			14.5	0.57	145	2100	580	8410	45	1.77	0.16	
8	5/16"			16.8	0.66	130	1880	520	7540	55	2.17	0.19	
10	3/8"			18.6	0.73	110	1590	440	6380	70	2.76	0.24	
12	1/2"			22.5	0.89	93	1340	372	5390	85	3.35	0.32	
16	5/8"			26.2	1.03	80	1160	320	4640	105	4.13	0.39	
19	3/4"			29.5	1.16	70	1010	280	4060	130	5.12	0.52	
25	1"			36.0	1.42	55	790	220	3190	150	5.91	0.66	
31	1.1/4"			43.5	1.71	45	650	180	2610	190	7.48	1.05	
38	1.1/2"			63.8	2.50	40	580	160	2320	240	9.45	1.25	
51	2"			73.0	2.87	33	470	132	1910	300	11.81	1.65	