

PH472-STEAM 2W/B 蒸汽管



Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W kg/m
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	
BR472-06	-06	10	3/8	10.0	0.77	19.5	290	20	2610	180	5.1	130	0.421
BR472-08	-08	12	1/2	12.5	0.91	23.0	290	20	2610	180	5.9	150	0.589
BR472-12	-12	19	3/4	19.0	1.18	30.0	290	20	2610	180	9.1	230	0.846
BR472-16	-16	25	1	25.4	1.45	36.8	290	20	2610	180	11.8	300	1.095
BR 472-20	-20	32	1.1/4	31.5	1.71	43.5	290	20	2610	180	14.8	375	1.505
BR 472-24	-24	38	1.1/2	38.0	1.95	49.5	290	20	2610	180	17.9	455	1.780
BR472-32	-32	51	2	51.0	2.52	64.0	290	20	2610	180	23.6	600	2.261
BR472-40	-40	63	2.1/2	63.0	3.27	83.0	290	20	2610	180	26.6	675	4.214
BR472-48	-48	76	3	76.0	3.86	98.0	290	20	2610	180	28.5	725	4.962

结构

- 内胶层: 黑色导电EPDM
- 加强层: 双钢丝编织
- 外胶层: 红色, EPDM 橡胶耐热和耐候
- 应用: 290 psi 恒定压力下的高温蒸汽管线
- 温度范围:连续: 高达 +210 °C 蒸汽